

Appl. No.: 09/523,446
Amdt. dated January 27, 2004
Reply to Office action of November 19, 2003

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Canceled).

2. (Previously presented) A method as in claim 27 wherein said data warehouse has a call table and a profile table, wherein the step of generating a calling profile cube based on the records further comprises the steps of:

retrieving records from the call table and based thereon generating a snapshot cube representing the records from the call table, said snapshot cube having predetermined dimensions;

retrieving records from the profile table and based thereon generating a profile cube representing the records from the profile table, said profile cube having predetermined dimensions that are the same as the dimensions of the snapshot cube;

merging the snapshot cube and the profile cube to generate an updated profile cube; and

deriving the volume-based calling pattern cubes based on the updated profile cube.

3. (Previously presented) A method as in claim 27 wherein the step of when the volume-based calling pattern cube is in a first predetermined relationship with predetermined fraudulent volume-based calling pattern, performing a first action includes one of:

flagging a particular caller with the volume-based calling pattern being analyzed as suspicious;

automatically generating an alert that specifies callers with suspicious volume-based calling pattern;

Appl. No.: 09/523,446
Amdt. dated January 27, 2004
Reply to Office action of November 19, 2003

performing further investigation on callers with suspicious volume-based calling pattern;

cancellation of telephone services for callers with suspicious volume-based calling pattern; and

performing other appropriate remedial actions.

4. (Previously presented) A method as in claim 27 further comprising:
analyzing the calling pattern cube by utilizing at least one OLAP operation.
5. (Previously presented) A method as in claim 4 wherein said OLAP operations is one of a roll-up operation, a drill-down operation, a dice operation, a slice operation, and an ad-hoc query.
6. (Previously presented) A method as in claim 27 wherein the predetermined fraudulent volume-based calling pattern in one of a personalized calling pattern and a group-based pattern.
7. (Previously presented) A method as in claim 2 further comprising:
storing the updated profile cube into the profile table in the data warehouse; and
performing data staging between the profile table and the updated profile cube at predetermined time intervals.
8. (Previously presented) A method as in claim 2 wherein said profile cube, snapshot cube, and updated profile cube each includes at least two dimensions and at least two levels.
9. (Previously presented) A method as in claim 8 further comprising:
analyzing the calling pattern cube by utilizing at least one OLAP operation along more than one level.

Appl. No.: 09/523,446
Amdt. dated January 27, 2004
Reply to Office action of November 19, 2003

10. (Previously presented) A method as in claim 8 further comprising:
analyzing the calling pattern cube by utilizing at least one OLAP operation
along more than one dimension.

11. (Previously presented) A method as in claim 2 wherein the profile cube,
snapshot cube, and the updated profile cube each are multi-level and multi-
dimensional cubes.

12. (Previously presented) A method as in claim 2 wherein the profile table
and the call table each has a plurality of attributes, and the profile cube and
snapshot cube each has a plurality of dimensions, said attributes corresponding
in a one-to-one fashion to the dimensions.

13. (Previously presented) A method as in claim 2 wherein the profile cube
includes at least one cell having probability based values.


14. (Previously presented) A data processing system comprising:
a data warehouse for storing data in a relational format, said data
warehouse including a profile table and a call table;
an OLAP server, coupled to the data warehouse, for providing
predetermined OLAP operations; and
a profile engine, coupled to the data warehouse for computing, maintaining
and utilizing caller pattern cubes that represent caller profiles; wherein the caller
pattern cubes can be utilized to detect telecommunication fraud.

15. (Previously presented) A data processing system as in claim 14 further
comprising:
a fraud detection module for detecting telecommunication fraud by
comparing known fraudulent profiles to caller pattern cubes;
the profile engine further generating a profile cube from information
selected from the profile table, generating a snapshot cube, updating the profile

Appl. No.: 09/523,446
Amdt. dated January 27, 2004
Reply to Office action of November 19, 2003

cube by merging the profile cube and the snapshot cube to generate an updated profile cube, and deriving a calling pattern cube based on the updated profile cube; wherein the profile engine is a scalable computation engine that is implemented by OLAP programming supported by the OLAP server.

16. (Previously presented) A data processing system as in claim 14 further comprising:

 an analysis tool for use by a data analyst to perform one of comparing the calling pattern cube to known fraudulent calling pattern cube and extracting information from the calling pattern cube based on selected dimensions, levels, and ad-hoc queries provided by the data analyst.

17. (Previously presented) A data processing system as in claim 14 further comprising:

a visualization tool for use by a data analyst to display the calling pattern cube in different formats, levels, and dimensions.

18. (Previously presented) A data processing system as in claim 14 further comprising:

a data staging tool for transferring data between the profile cube stored in the OLAP server and profile table in the data warehouse at predetermined time intervals.

19. (Canceled).

20. (Previously presented) A method as in claim 27 further comprising:

utilizing an OLAP server to create a calling profile cube, updated calling profile cubes, derive calling pattern cubes from the calling profile cube, analyzing calling pattern cubes, and comparing calling pattern cubes;

Appl. No.: 09/523,446
Amdt. dated January 27, 2004
Reply to Office action of November 19, 2003

wherein OLAP programming supported by the OLAP server provides a scalable computation engine for generating and processing the calling pattern cubes.

21. (Canceled).

22. (Previously presented) The method of claim 28 wherein the calling profile cube is a multi-dimensional and a multi-level cube and wherein the volume-based calling pattern cubes are multi-dimensional and a multi-level cubes.

23. (Previously presented) The method of claim 28 further comprising:
performing data staging at predetermined time intervals; and
updating the calling profile cube by generating a snapshot cube from a call table; and
merging the snapshot cube with the calling profile cube to generate an updated calling profile cube.

24. (Previously presented) The method of claim 28 wherein the calling profile cube has a cell that includes a probability distribution value based on one of the probability distribution on calls to each callee and the probability distribution on all calls.

25. (Previously presented) The method of claim 22 wherein the dimensions include a day-of-week hierarchy, a time hierarchy, and a duration hierarchy.

26. (Canceled).

27. (Previously presented) A method for detecting telecommunication fraud performed in a data processing system having a data warehouse and an OLAP server, the method comprising:

retrieving a plurality of call records from the data warehouse;

Appl. No.: 09/523,446
Amdt. dated January 27, 2004
Reply to Office action of November 19, 2003

generating a calling profile cube based on the call records; wherein the calling profile cube includes information on multiple customers;
generating a volume-based calling pattern cube for each individual customer based on the multi-customer calling profile cube;
comparing the volume-based calling pattern cube for each customer to a predetermined fraudulent volume-based calling pattern; and
when the volume-based calling pattern cube is in a first predetermined relationship with predetermined fraudulent volume-based calling pattern, performing a first action.

28. (Previously presented) A method for detecting telecommunication fraud performed in a data processing system having a data warehouse and an OLAP server, the method comprising:

retrieving a plurality of call records from the data warehouse;
generating a calling profile cube based on the call records; wherein the calling profile cube includes information on multiple customers;
generating a volume-based calling pattern cube for each individual customer based on the multi-customer calling profile cube;
generating a probability-based calling pattern cube based on the volume-based calling pattern cube for each individual customer;
comparing the probability-based calling pattern cube for each customer to a predetermined fraudulent probability-based calling pattern;
when the probability-based calling pattern cube is in a first predetermined relationship with predetermined fraudulent probability-based calling pattern, performing a first action.

29. (Previously presented) A method as in claim 28 wherein the step of when the probability-based calling pattern cube is in a first predetermined relationship with predetermined fraudulent probability-based calling pattern, performing a first action includes one of:

Appl. No.: 09/523,446
Amdt. dated January 27, 2004
Reply to Office action of November 19, 2003

flagging a particular caller with the probability-based calling pattern being analyzed as suspicious;
automatically generating an alert that specifies callers with suspicious probability-based calling pattern;
performing further investigation on callers with suspicious probability-based calling pattern;
cancellation of telephone services for callers with suspicious probability-based calling pattern; and
performing other appropriate remedial actions.

30. (Previously presented) The method of claim 29 wherein the probability-based calling patterns enables one of the analysis and comparison of a first probability-based calling patterns that covers a first time period with a second probability-based calling patterns that covers a second time period.

31. (New) A system, comprising:
a data warehouse that stores call records; and
a computer system coupled to the data warehouse, the computer system receives the call records and maintains a caller profile cube for use with detecting telecommunication fraud;
wherein the caller profile cube comprises a combination of a profile cube and a snapshot profile cube.

32. (New) The system of claim 31 wherein the caller profile cube is periodically updated by combining the caller profile cube with a new snapshot profile cube generated from new call records.

33. (New) The system of claim 31 wherein the computer system uses OLAP programming to maintain the caller profile cube.

Appl. No.: 09/523,446
Amdt. dated January 27, 2004
Reply to Office action of November 19, 2003

b¹
34. (New) The system of claim 31 wherein the computer system uses calling parameters to generate probability-based calling pattern cubes for use with detecting telecommunication fraud.

35. (New) The system of claim 34 wherein the calling parameters comprise at least one of a call duration, a time of day, a day of week, and a number of calls.
